




Receiver Door Latches



Receiver Travel Door





Receivers Ready For Deployment



• FleetGenius manufactures compactor receiver containers in a variety of sizes and designs to best fit the application.

- Octagonal, Rectangular, Heavy Duty, and Specialty Receivers to meet standard and custom specifications.
 - Standard "Octagon" Receivers are recommended to promote a "rolling motion" inside during compaction resulting in full containers and maximized payloads.
 - "Bakers Guard" Protective Coating is sprayed on the understructure for improved durability.







Visit us at www.fleetgenius.com for more details or call us toll free at 800-221-4153.



COMPACTOR RECEIVER CONTAINERS

CHOOSE THE SIZE COMPACTOR RECEIVER CONTAINER THAT FITS YOUR NEEDS.



OCTAGON COMPACTOR RECEIVERS						
MODEL NO.	CAPACITY	OVERALL LENGTH	OVERALL HEIGHT	overall Width		
CC30-710	30 YD	17 FT	105 IN	96 IN		
CC40-710	40 YD	22 FT	105 IN	96 IN		
CC44-710	44 YD	24 FT	105 IN	96 IN		
RECTANGULAR COMPACTOR RECEIVERS						

MODEL NO.	CAPACITY	OVERALL LENGTH	OVERALL HEIGHT	OVERALL WIDTH
CC42R	42 YD	22 FT	105 IN	96 IN

Standard Octagonal Specifications

- Understructure Cross members 3" channel 4.1# per foot on 16" center
- 2 Gussets per cross member
- Main Rails 2" x 6" tubing 1/4" wall, with solid bull nose
- Pull Hook 1.5" integrated and welded into sub-structure crossmembers
- Floor 3/16" steel plate
- Wheels 8" dia. x 6" long with grease fitting
- Guide Rollers 4" dia. x 6" long with recessed grease fitting
- Sides and Front 3/16" steel plate
- Sides and Top -10 gauge
- Rear Door 3/16" steel w/ 3-point lever latch and safety chain w/ 6" formed channel frame
- Hinges 3 heavy duty 8" x 8" plate hinges w/ 1.5" pin and grease zerks
- Paint Oxide primer outside 2.0 mils; industrial enamel finish to 2.0 mils

Optional Features

- Rectangular Designs
- Heavy Duty Specifications
- Belly Bands
- Travel Doors
- Sealed Doors
- Cable Ejection System (cardboard)

Visit us at www.fleetgenius.com for more details or call us toll free at 800-221-4153.